

Session 5

Erosion and Sediment Control Best Management Practices (BMPs)

1

Centre for Environmental Training cet

Overarching Principles

Erosion control is the key!!!

Manage Water

- Look up, around and down
- Assess where water comes from, how it will move through the site, and where it ends up

Manage Soils

- Understand soil erodibility – some soils are more erodible than others
- Protect soils accordingly

2

Centre for Environmental Training cet

Best Management Practice

Remember, erosion control is far more effective than sediment control and should be prioritised

This section outlines a range of general procedures and Best Management Practices (BMPs) for erosion and sediment control

3

Centre for Environmental Training cet

Planning

Planning considerations:

- Limit construction activities to the shortest practical duration
- Restrict active works areas to a manageable size
- Plan for diversion of run-on stormwater

4

Centre for Environmental Training cet

Scheduling

On sensitive or high erosion hazard sites, if possible plan construction for times when the rainfall activity is typically lower (e.g. April – October)

High erosion hazard site >500 t/ha/yr calculated soil loss using RUSLE

Be prepared though, heavy rain can occur at any time of year!

5

Centre for Environmental Training cet

Reduce Disturbance Areas

- Stage development where practical, reducing the area exposed to erosion at any one time
- Limit disturbance to 5m (preferably 2m) from essential work areas
- Use barrier fence (upslope) and sediment fence (downslope) to define work areas and “no-go” zones

6

Centre for Environmental Training cet



Managing Water Catch Drains/Diversion Banks

9

Centre for Environmental Training cet

Purpose

- Divert clean stormwater around works areas and help keep work areas dry
- Capture and convey dirty water to sediment traps
- General stormwater conveyance
- Shorten slope lengths
- Temporary or permanent features
- Very important tool in erosion control!

10

Centre for Environmental Training cet

Perimeter Bank

11

Centre for Environmental Training cet

Catch Drains

12

Centre for Environmental Training cet

Erosion Blankets



13

Centre for Environmental Training cet

Bitumen Spraying



14

Centre for Environmental Training cet

Sprayed Concrete



15

Centre for Environmental Training cet

Check Dams



16

Centre for Environmental Training cet

Purpose

- Reduce velocity of flow in channels, reducing erosive energy
- Can provide moderate filtering/trapping capacity for coarse sediment
- Longer detention times can allow settling of some fine sediment, but this would almost certainly be re-eroded unless removed after each storm

17

Centre for Environmental Training cet

Turf Lining and Check Dams



18

Centre for Environmental Training cet

Check Dams



19

Centre for Environmental Training cet

Example – ‘Geo-ridge’



20

Centre for Environmental Training cet

Example – biodegradable logs



21

Centre for Environmental Training cet

Maintenance

- Check for erosion problems during and after rain, especially at inlets and outlets
- Repair scoured areas and line with erosion resistant materials
- Remove accumulated sediment
- Provide new drains as construction proceeds to new areas
- Look for signs of localised flooding and redesign drains if necessary

22

Centre for Environmental Training cet

Inlet Protection



23

Centre for Environmental Training cet

Protected Outlet



24

Centre for Environmental Training cet

Failed Inlet Protection



25

Centre for Environmental Training cet

Stabilised Access

- Establish a single stabilised site access
- Helps limit disturbance and reduce erosion at a high traffic point(s)
- Reduces sediment tracking to road
- Reduces down-time after rain

26

Centre for Environmental Training cet



Maintenance

- Even out wheel ruts
- Remove sediment from sediment basin and replace or resurface gravel periodically
- Repair surface drains
- Sweep the road

28

Centre for Environmental Training cet

Stockpiles

- Store topsoil and subsoil separately
- Understand dispersive soil types (typically subsoils) – do not mix
- Preserve seed viability and soil structure (minimise re-working)
- Control erosion and prevent sediment pollution
- Longer term stockpiling – mulch cover or revegetation is a good option

29

Centre for Environmental Training cet



Construction / Maintenance

- Place at least 2 m from property boundaries and hazard areas (e.g. waterways, roads, existing vegetation)
- Place stormwater diversion drains upslope and sediment fence downslope
- Keep height < 2 m if possible, and batters with 2:1 maximum slope
- Stabilise stockpiles that are in place for more than 10 days using vegetation or cover (~60% effective cover)

31 Centre for Environmental Training cet



Stockpiles

33 Centre for Environmental Training cet

Example Poor Practice

34 Centre for Environmental Training cet

Example Poor Practice

35 Centre for Environmental Training cet

Sediment and Pollution Control BMPs

- Erosion controls must be a major priority at any development site, but inevitably are not 100% effective
- Sediment controls act along with good erosion control to minimise off-site pollution, as part of an overall “treatment train”
- Helps keep nutrients, heavy metals, litter and waste from leaving the site

36 Centre for Environmental Training cet

Keeping Contaminants On-site



37

Centre for Environmental Training cet

Soil Type and Sediment Trapping Effectiveness

- The coarser the sediment, the easier to trap (generally)
- Effective capture of finer silts and clays requires long detention times and/or flocculation
- Dispersible sediments in particular may never settle out except with flocculation!

38

Centre for Environmental Training cet

Catchment and Runoff Characteristics

- For smaller catchments (<4,000m²) small sediment traps (e.g. sediment fence) can be used to good effect if designed and installed properly
- Larger catchments require much larger traps (i.e. sediment basins)
- Possible to estimate sediment yield to help size sediment traps
- Keep traps offline (avoid concentrated flow) and divert clean water to improve effectiveness

39

Centre for Environmental Training cet

Function of Sediment Traps

- Sediment traps generally work by reducing flow velocities, allowing sediment and other pollutants time to settle
- It is a common misconception that traps work by “filtering” water (although this is a partial mechanism in some traps)

40

Centre for Environmental Training cet

Maintenance of Sediment Traps

- Inspect devices after each storm and:
 - remove sediment when sediment reaches 1/3 to 1/2 capacity
 - repair damage
 - assess effectiveness and install additional erosion and sediment controls as required
 - flocculate sediment basins capturing fine or dispersible sediment

41

Centre for Environmental Training cet

Turf Filter Strips



Recently laid turf filter strip. Note the returns that prevent water flowing along the strip

42

Centre for Environmental Training cet

Sediment Fence



43

Centre for Environmental Training cet

Sediment Fence



44

Centre for Environmental Training cet

Purpose

- Use downslope of all disturbed areas
- Construct along the contour to prevent water concentrating at one point
- Best used to dam water where it is inclined to pond (e.g. flat areas at base of batters)
- Designed for sheet flow, not concentrated flow
- Not appropriate in waterways

45

Centre for Environmental Training cet

Effectiveness

- Sediment fence typically has pore openings typically ~ 0.035mm
- Clay and silt are <0.02mm and much will pass straight through
- Sand >0.02mm and gravel caught with greater efficiency
- Trapped material will improve efficiency to a point.....maintenance required to ensure continued performance

46

Centre for Environmental Training cet

Poor Location?



47

Centre for Environmental Training cet

Example - Good Practice



48

Centre for Environmental Training cet

Inappropriate Use



49 Centre for Environmental Training cet

Repairs Required



Sediment fence needs replacing. Note the sediment escaping through torn section

50 Centre for Environmental Training cet

Gravel Sausages and Kerb Inlet Filters



51 Centre for Environmental Training cet

Purpose

- Used to protect kerb-side stormwater inlets, grated drains etc.
- Can be moderately effective at trapping coarse sediment when selected, installed and maintained correctly
- Remove sediment regularly otherwise it will be re-mobilised
- Take care to avoid causing downstream flooding

52 Centre for Environmental Training cet

Example – Good Practice



53 Centre for Environmental Training cet

Example – Good Practice



Image: Strategic Environmental and Engineering Consulting (SEEC)

54 Centre for Environmental Training cet

Example – Good Practice



Image: Naco Civil

55 Centre for Environmental Training cet

Example – Good Practice



56 Centre for Environmental Training cet

Inadequate Maintenance



Sausage damaged probably by vehicles, now contributes to sediment pollution

57 Centre for Environmental Training cet

Innovative Ideas



58 Centre for Environmental Training cet

Filter Bags



59 Centre for Environmental Training cet

Purpose

- Place at end of pipes to filter sediment
- Use when dewatering pits, trenches and sediment traps
- Locate in a well grassed area away from waterways during use
- max. pore size ~0.2mm (sands and some silts)

60 Centre for Environmental Training cet

Dewatering – example



61

Centre for Environmental Training cet


Dewatering – example



62

Centre for Environmental Training cet


Example – ‘U’ Traps



63

Centre for Environmental Training cet

Example – ‘U’ Traps



64

Centre for Environmental Training cet

Example – Minor Works



65

Centre for Environmental Training cet

Example – Major Works



66

Centre for Environmental Training cet